



# MATERIAL SAFETY DATA SHEET

## MSDS # 8-HD3

### *ARCTIC FIRE PREMIUM PLUS 15W40*

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**TRADE NAME:** Premium Plus 15W40

**APPLICATIONS:** Lubricating Oil, Crankcase Oil

**SYNONYMS:** Automotive Motor Oil

**CAS REGISTRY #:** NA

**CHEMICAL FAMILY:** Automotive Motor Oil

**EMERGENCY PHONE:** CHEMTREC – (800) 424-9300 or (703) 527-3887 (collect)

**SUPPLIER:** Sinclair Oil Corporation  
P.O. Box 30825  
Salt Lake City, Utah 84130

**TELEPHONE / FAX:** (888) 340-3466 / (801) 524-2740

## 2. COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENTS:	CAS#	Typical wt.%
Non-hazardous mixture of components in highly refined base oil		97-99.0
Zinc C <sub>1</sub> C <sub>14</sub>	68649-42-3	1-3.0

## 3. HAZARDS IDENTIFICATION

**APPEARANCE:** Amber, transparent, Non-Viscous Fluid

**PHYSICAL STATE:** Liquid

**ODOR:** Mild, bland, hydrocarbon odor

**EMERGENCY OVERVIEW:** Avoid contact with used motor oil. Avoid prolonged breathing of vapor, mist, or gas, clean oil-soaked clothing before reuse, wash thoroughly after handling

**POTENTIAL HEALTH EFFECTS:** May cause minimal irritation

**INHALATION:** Vapors or mist, in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness.

**EYE CONTACT:** May cause minimal irritation, experienced as temporary discomfort.

**SKIN CONTACT:** May cause minimal irritation, experienced as temporary discomfort.

**INGESTION:** If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.

## 4. FIRST AID MEASURES

**INHALATION:** If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or respiratory irritation persists.

**EYE CONTACT:** Flush immediately with water for at least 15 minutes. Seek medical attention if irritation develops or persists.

**SKIN CONTACT:** Discard contaminated leather articles. Wash contact areas with soap and water. Launder contaminated clothing before reuse.

**INGESTION:** If more than several mouthfuls of this material are swallowed, give two glasses of water (16 oz.). Get medical attention.

## 5. FIRE FIGHTING MEASURES

**FLASH POINT (°F):** 442°F (228°C)

**FLAMMABLE LIMITS:** LEL – not determined UEL – not determined

**AUTOIGNITION TEMPERATURE:** not determined

**FLAMMABILITY CLASSIFICATION:** Combustible Liquid

**GENERAL HAZARD:** No unusual or explosive hazards

**FIRE FIGHTING INSTRUCTIONS:** Use water spray, dry chemical, foam, or carbon dioxide to extinguish flames. Use water spray to cool fire-exposed containers. Water or foam may cause frothing.

**FIRE FIGHTING EQUIPMENT: HAZARDOUS COMBUSTION PRODUCTS:** Use of SCBA in enclosed or confined spaces, or as other wise needed (Bunker gear).

**Hazardous Decomposition Products:** May produce carbon monoxide

## 6. ACCIDENTAL RELEASE MEASURES

**LAND SPILL:** Treat spill as an oil spill. Remove leaking containers to a safe area. Contain and remove by mechanical means. Guard against contamination of water supplies. Spilled material, made solid by using an inert substance, may be scraped up from the ground. Report spills to appropriate authorities. Dispose of in accordance with Federal, State, and Local regulations.

**WATER SPILL:** Treat spill as an oil spill. Spill may be removed from water with boom and vacuuming equipment. Report spills to appropriate authorities. Dispose of in accordance with Federal, State, and Local regulations.

## 7. HANDLING AND STORAGE

**HANDLING / STORAGE:** Minimum feasible handling temperatures should be maintained. / Periods of exposure to high temperatures should be minimized. Water contamination should be avoided.

## 8. EXPOSURE CONTROLS, RESPIRATORY & PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Provide ventilation sufficient to prevent exceeding recommended exposure limits

**PERSONAL PROTECTION:**

**PROTECTIVE CLOTHING:** Use full-face shield or chemical goggles, impervious gloves, and boots.

**RESPIRATOR:** Airborne concentrations should be kept to lowest levels possible. If vapor, mist or dust is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air-supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown.

### **OCUPATIONAL EXPOSURE LIMITS**

COMPONENT	LIMIT	TWA	STEL	CEILING	NOTATION	OTHER
Mineral Oil Mist	OSHA	5mg/M <sup>3</sup>				
Mineral Oil Mist	ACGIH	0.2mg/M <sup>3</sup>	10mg/M <sup>3</sup>			A4

A1= Confirmed Human Carcinogen  
A3= Confirmed Animal Carcinogen with Unknown Relevance to Humans  
A4= Not Classified as a Human Carcinogen  
CNS= Central Nervous System  
Skin= Absorption through the skin may contribute to overall exposure

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE/PHYSICAL STATE:** Liquid

**COLOR:** tan liquid

**DENSITY/SPECIFIC GRAVITY (g/ml):** 0.9

**VAPOR DENSITY (air=1):** Greater than 5

**VAPOR PRESSURE:** <1 PSIA

**BOILING POINT/RANGE:** above 600 F.

**SOLUBILITY IN WATER:** No

**VISCOSITY:** N/A/F

**pH :** N/A

**FREEZING POINT:** NA

## 10. STABILITY AND REACTIVITY

**GENERAL:** This product is stable

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:** Strong oxidizers.

**HAZARDOUS DECOMPOSITION:** Incomplete burning can produce carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

**SYSTEMIC:** Petroleum derived fuel oils are complex and variable mixtures of hydrocarbons. In general, the more viscous the mixture, the less toxic it will be.

**ACUTE:**

**Inhalation:** : Not determined

**Ingestion:** LD50 Believed to be > 5.00 g/kg (rat) practically non-toxic

**Eye:** (Draize) Believed to be < 15 /110 (rabbit) no appreciable effect

**Skin:** LD50 Believed to be > 2.00 g/kg (rabbit) practically non-toxic

**CHRONIC:** No data available to indicate the product or its components present a chronic health hazard

## 12. DISPOSAL INFORMATION

**RCRA:** Dispose of this product in accordance with local and/or national regulations.

EPA Hazard Class: Not determined

Dispose of in accordance with Federal, State, and Local regulations.

### 13. TRANSPORT INFORMATION

DOT (Department of Transportation): Not regulated

PROPER SHIPPING NAME:

HAZARD CLASS: Not classified as hazardous material for shipping

IDENTIFICATION NUMBER: NA

NAERG96 NUMBER: NA

### 14. REGULATORY INFORMATION

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): NA

SARA TITLE III (Superfund Amendments and Reauthorization Act):

### 15. OTHER INFORMATION

NFPA 704/HMIS:

Health – 1 Flammability – 1 Reactivity – 0  
(0 = insignificant, 1 = slight, 2 = moderate, 3 = high, 4 = extreme)

REVISION SUMMARY:

Complete review of MSDS, December 2005.

**THIS PRODUCT MATERIAL SAFETY DATA SHEET PROVIDES HEALTH AND SAFETY INFORMATION. THE PRODUCT SHOULD BE USED IN APPLICATIONS CONSISTENT WITH THIS PRODUCT LITERATURE. FOR ANY OTHER USES, EXPOSURES SHOULD BE EVALUATED SO THAT APPROPRIATE HANDLING PRACTICES AND TRAINING PROGRAMS CAN BE ESTABLISHED TO ENSURE SAFE WORKPLACE OPERATIONS.**

**THIS MATERIAL SAFETY DATA SHEET IS PROVIDED IN GOOD FAITH AND MEETS THE REQUIREMENTS OF THE HAZARDOUS COMMUNICATION PROVISIONS OF SARA TITLE III AND 29CFR1910.1200(g) OF THE OSHA REGULATIONS. THE ABOVE INFORMATION IS BASED ON REVIEW OF AVAILABLE INFORMATION SINCLAIR BELIEVES IS RELIABLE AND IS SUPPLIED FOR INFORMATIONAL PURPOSES ONLY. SINCLAIR DOES NOT GUARANTEE ITS COMPLETENESS OR ACCURACY. SINCE CONDITIONS OF USE ARE OUTSIDE THE CONTROL OF SINCLAIR, SINCLAIR DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, AND ANY LIABILITY FOR DAMAGE OR INJURY WHICH RESULTS FROM THE USE OF THE ABOVE DATA. NOTHING HEREIN IS INTENDED TO PERMIT INFRINGEMENT OF VALID PATENTS AND LICENSES.**

DATE: December 2005