

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name:	Sinclair Industrial EP ISO 150
Product Code:	SI621555 (Sinclair Code: 561-003)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:Gear OilRecommendedNot applicablerestrictions:Image: Contract of the second second

### 1.3 Details of the supplier of the safety data sheet

1.5. Details of the supplier of the safety data sheet		
Manufacturer:	Warren Distribution, In	IC.
	727 S. 13th Street	
	Omaha, NE 68102	
Information Phone:	+01 (800) 825-1235	+01 (402) 341-9397
E-mail:	sds@wd-wpp.com	

# 1.4. Emergency telephone numberEmergency phone number:CHEMTREC: +1 (800) 424-9300International: +01 (703) 527-3887

### **SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture** Not classified under GHS

2.2. Label elements

### 2.3. Other hazards

Hazards not otherwise Avoid prolonged or repeated skin contact with used fluid. classified:

### Unknown acute toxicity (GHS-US)

SECTION 3: Composition/information on ingredients			
Chemical Name	%	CAS #	GHS Classification
Residual oils (petroleum), solvent dewaxed	40 - 70	64742-62-7	Acute Tox. 4; H332
			Acute Tox. 3; H331
~		GER 4040 4000 (77	

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

SECTION 4: First aid measures		
4.1. Description of first aid measures		
Inhalation	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.	
Eyes	None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.	
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists. Seek medical advice if symptoms persist.	
Ingestion	Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this SDS.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms	Not determined	
4.3. Indication of any immediate medical attention and special treatment needed		

### **SECTION 4: First aid measures**

Note to Doctor

Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable and Unsuitable	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may	
Extinguishing Media:	cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied	
	to the surface of the fire. Do not direct a stream of water into the hot burning liquid.	
5.2. Special hazards arising fr	om the substance or mixture	
Fire and/or Explosion	Material may be ignited only if preheated to temperatures above the high flash point, for example in	
Hazards	a fire.	
5.3. Advice for firefighters		
Fire Fighting Methods and	Do not enter fire area without proper protection including self- contained breathing apparatus and	
Protection	full protective equipment. Use methods for the surrounding fire.	
Hazardous Combustion	Carbon monoxide, Smoke	
Products		

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**General Measures:** No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.

#### **6.2. Environmental precautions**

Do not flush to sewer.

Avoid runoff into storm sewers and ditches that lead to waterways.

Remove from water surface by skimming or with suitable absorbents. Do not use dispersants.

Avoid runoff into storm sewers and ditches that lead to waterways.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up:** Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. {EMSFORM\_06GHS\_CLEAN}

### 6.4. Reference to other sections

Follow all protective equipment recommendations provided in Section 8.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Mildly irritating material. Avoid unnecessary exposure.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool dry place. Isolate from incompatible materials.

**Incompatible materials** 

See Section 10.

**7.3. Specific end use**(s) Gear Oil

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Chemical Name Oil mist, mineral Oil mist, mineral Oil mist, mineral None. None. Occupational Exposure Limits OSHA PEL ACGIH TLV-TWA ACGIH STEL IDLH OSHA PEL-Skin Notation Value 5 mg/m3 5 mg/m3 10 mg/m3

#### 8.2. Exposure controls

Sinclair Industrial EP ISO 150

8.2. Exposure controls	
Engineering Measures	Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.
<b>Respiratory Protection</b>	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.
<b>Respirator Type(s)</b>	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.
Eye Protection	No special requirements under normal industrial use.
Skin Protection	Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves	Neoprene, Nitrile

### **SECTION 9: Physical and chemical properties**

1. Information on basic physic	cal and chemical properties
Physical State	Liquid
Color	Brown
Odor	Mild
Odor threshold	Not determined
H	Not determined
Freezing point	Not determined
Boiling Point	Not determined
Flash Point (°C)	221
Slash Point Method	COC
Evaporation Rate	Not determined
<b>Jpper Flammable/Explosive</b>	= 10
Limit, % in air	
Lower Flammable/Explosive	=1
Limit, % in air	
Flammability (solid, gas)	Not applicable
apor pressure	<0.20
Vapor Density	Not determined
Relative Density	0.88
Solubility in Water	Negligible; 0-1%
Octanol/Water Partition	Not determined
Coefficient	
Autoignition Temperature	Not determined
Decomposition Temperature	Not determined
Viscosity(°C)	145.7
0.2. Other information	
Volatiles, % by weight	0.000000

## SECTION 10: Stability and reactivity

10.1. Reactivity	No data available.
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous	Hazardous polymerization will not occur.
reactions	
10.4. Conditions to avoid	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
10.5. Incompatible materials	Strong oxidizing agents
10.6. Hazardous	Carbon monoxide, Smoke
decomposition products	

### **SECTION 11: Toxicological information**

### **SECTION 11: Toxicological information**

11.1. Information on toxicologi	cal effects
Ingestion Toxicity	No hazard in normal industrial use. Estimated to be $> 5.0$ g/kg.
Skin Contact	Likely to be non-irritating to skin based on animal data.Can cause minor skin irritation, defatting, and dermatitis.
Absorption	Likely to be practically non-toxic based on animal data.
Inhalation Toxicity	No hazard in normal industrial use. Likely to be practically non-toxic based on animal data.
Eye Contact	This material is likely to be non-irritating to eyes based on animal data. No hazard in normal industrial use.
Sensitization	Non-hazardous under Respiratory Sensitization category.No data available to indicate product or components may be a skin sensitizer.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive and	No data available to indicate product or any components present at greater than 0.1% may cause
<b>Developmental Toxicity</b>	birth defects.
Specific target organ toxicity-Single exposure	Non-hazardous under Specific Target Organ Systemic Toxicity Single Exposure category.
Specific target organ toxicity-Repeated exposure	Non-hazardous under Specific Target Organ Systemic Toxicity Repeated Exposure category.
Aspiration toxicity	Non-hazardous under Aspiration category.
Other information	No data available.

#### Agents Classified by IARC Monographs

Ethylene oxide	IARC Group 1
Not applicable	IARC Group 2A
Cumene	IARC Group 2B
ethylbenzene	IARC Group 2B
Vinyl acetate	IARC Group 2B
1,4-Dioxane	IARC Group 2B
Propylene oxide	IARC Group 2B

#### National Toxicity Program (NTP) Status

Ethylene oxide	Known Human Carcinogen
Cumene	Reasonably Anticipated To Be A Human Carcinogen
1,4-Dioxane	Reasonably Anticipated To Be A Human Carcinogen
Propylene oxide	Reasonably Anticipated To Be A Human Carcinogen

### **SECTION 12: Ecological information**

12.1. Toxicity
Acute Aquatic ecotoxicity: Non-hazardous under Aquatic Acute Environment category.
Chronic Aquatic ecotoxicity: Non-hazardous under Aquatic Chronic Environment category.
12.2. Persistence and degradability
Biodegrades slowly.
12.3. Bioaccumulative potential
Bioconcentration may occur.
12.4. Mobility in soil
This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
12.5. Results of PBT and vPvB assessment
No data available.
12.6. Other adverse effects
Not determined

### **SECTION 13: Disposal considerations**

### **SECTION 13: Disposal considerations**

**13.1.** Waste treatment methods

Disposal Methods Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil. Waste Disposal Code(s) Waste Description for Spent Product Spent or discarded material is non-hazardous according to environmental regulations. Contaminated packaging: Recycle containers whenever possible. Recycle containers whenever possible. Recycle containers whenever possible. Recycle containers whenever possible. Recycle containers whenever possible.

Recycle containers whenever possible.

### **SECTION 14: Transport information**

**DOT Basic** Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO). **Description** 

### **SECTION 15: Regulatory information**

### **Chemical Inventories**

TSCA Status	All components of this material are on the US TSCA Inventory or are exempt.
U.S. State Restrictions:	Not applicable
WHMIS:	Uncontrolled product according to WHMIS classification criteria.

	Describe discus	<b>C</b> • • <b>C</b>	0/
Chemical Name None.	<b>Regulation</b> CERCLA	CAS #	%
1,2,4-Trimethylbenzene	SARA 313	95-63-6	0.001-0.01
	SARA 313	1330-20-7	0.001- 0.01
Xylene (mixed isomers) Cumene			
Cument	SARA 313	98-82-8	0.001-0.01
ethylbenzene	SARA 313	100-41-4	0.001-0.01
Vinyl acetate	SARA 313	108-05-4	0.001-0.01
1,4-Dioxane	SARA 313	123-91-1	0.001-0.01
Ethylene oxide	SARA 313	75-21-8	0.001-0.01
Propylene oxide	SARA 313	75-56-9	0.001-0.01
None.	SARA EHS		
None.	TSCA 12b		
U.S. State Decrelations			
<u>U.S. State Regulations</u> Chemical Name	Dogulation	CAS#	%
	Regulation		, 0
Cumene	California Prop 65-	98-82-8	0.001- 0.01
.1 11	Cancer	100 41 4	0.001 0.01
ethylbenzene	California Prop 65-	100-41-4	0.001- 0.01
	Cancer		
1,4-Dioxane	California Prop 65-	123-91-1	0.001- 0.01
	Cancer		
Ethylene oxide	California Prop 65-	75-21-8	0.001-0.01
	Cancer		
Propylene oxide	California Prop 65-	75-56-9	0.001-0.01
	Cancer		
Ethylene oxide	California Prop 65- Dev.	75-21-8	0.001-0.01
2	Toxicity		
Ethylene oxide	California Prop 65-	75-21-8	0.001-0.01
	Reprod -fem		
Ethylene oxide	California Prop 65-	75-21-8	0.001-0.01
	Reprod-male	10 21 0	0.001 0.01
	Reprou-maie		

Chemical Nat None. None. None. None. None.	me	Mass New Penns Rhod Minn	llation achusetts RTK List Jersey RTK List sylvania RTK List e Island RTK List esota Hazardous cance List	CAS #		%		
		<b>HMIS Ratings:</b>		NFPA Ratings:				
		Health:	1	Health:	1			
		Fire: Reactivity:	$1 \\ 0$	Fire: Reactivity:	1 0			
		PPE:	B	Reactivity.	0			
			2					
	KEY:	0 - Least	1 - Slight	2 - Moderate	3 - High	4 – Extreme		
		r information						
Revision Date	9	10/22/2015 9:2 10/22/2015 9:2						
Supersedes: References				f Governmental Indu	strial Hygienists			
Kelefences			can Industrial Hygi		strai Hygiemsts			
			Federal Regulation					
		DOT: United States Department of Transportation GHS: Globally Harmonized System of Classification and Labeling of Chemicals HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transportation Association IDLH: Immediately Dangerous to Life or Health IMDG: International Maritime Dangerous Goods NFPA: National Fire Protection Association NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program						
	OSHA: Occupational Safety and Health Administration							
PEL: Permissible Exposure Limit RTK: Right-to-Know SADA: Superfund Amondments and Deputherization Act								
					A at			
		SARA: Superfund Amendments and Reauthorization Act STEL: Short-term Exposure Limit						
		TLV: Threshold limit value						
		TSCA: Toxic Substances Control Act						
		TWA: Time weighted average						
		UN: United Nations						
	WHMIS: Workplace Hazardous Materials Information System							
Disclaimer		THIS PRODUCT MATERIAL SAFETY DATA SHEET PROVIDES HEALTH AND SAFETY						
			INFORMATION. THE PRODUCT SHOULD BE USED IN APPLICATIONS CONSISTENT WITH THIS PRODUCT LITERATURE. FOR ANY OTHER USES, EXPOSURES SHOULD BE					
		EVALUATED SO THAT APPROPRIATE HANDLING PRACTICES AND TRAINING						
		PROGRAMS CAN BE ESTABLISHED TO ENSURE SAFE WORKPLACE OPERATIONS.						
		THIS MATERIAL SAFETY DATA SHEET IS PROVIDED IN GOOD FAITH AND MEETS THE						
		REQUIREMENTS OF THE HAZARDOUS COMMUNICATION PROVISIONS OF SARA TITLE						
			III AND 29 CFR 1910.1200(g) OF THE OSHA REGULATIONS. THE ABOVE INFORMATION IS BASED ON REVIEW OF AVAILABLE INFORMATION SINCLAIR BELIEVES IS RELIABLE					
			AND IS SUPPLIED FOR INFORMATIONAL PURPOSES ONLY. SINCLAIR DEELEVES IS RELIABLE					
		GUARANTEE ITS COMPLETENESS OR ACCURACY.						
		SINCE CONDITIONS OF USE ARE OUTSIDE THE CONTROL OF SINCLAIR, SINCLAIR						

### **SECTION 16: Other information**

DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, AND ANY LIABILITY FOR DAMAGE OR INJURY WHICH RESULTS FROM THE USE OF THE ABOVE DATA. NOTHING HEREIN IS INTENDED TO PERMIT INFRINGEMENT OF VALID PATENTS AND LICENSES.