

TWO-CYCLE ENGINE OIL

Sinclair Arctic Fire 2-Cycle Engine Oil is a premium quality lubricant which provides outstanding protection for 2-Cycle engines including those powering outboard motors, lawnmowers, weed trimmers, motorcycles, chainsaws, snowmobiles and other equipment. Because of the unique solvent system used in Sinclair Arctic Fire 2-Cycle Engine Oil, this product is not required to be labeled "COMBUSTIBLE."



APPLICATIONS

- 2-cycle outboard motors including those with oil injection systems or those requiring pre-mixing up to 50:1 ratio and beyond.
- 2-cycle lawnmower engines.
- Two-cycle snowmobile engines requiring an SAE Miscibility/Fluidity Grade 3 lubricant, readily mixes with fuel, or is pumpable at temperatures down to -13 °F.
- Motorcycles with 2-cycle engines.
- Golf carts with 2-cycle engines.

- Most chain saws, weed trimmers, edgers and other equipment, which are powered with 2-cycle engines.
- Ashless type oil for water-cooled engines.

WARNING: NOT FOR USE IN 4-CYCLE ENGINES

PERFORMANCE

- Helps Extend Engine Life Increased detergency and provides better overall engine cleanliness and extended engine life. Lessens ring sticking and piston deposits.
- Reduces Friction Friction reduction of at least 10% over TC-WII engine oils for better protection against scuffing and piston seizure, and better protection at lean fuel: oil ratios.
- Outstanding Performance Even in high horsepower 2-cycle engines.
- Performs Reliably in Most 2-cycle Engine Types Delivers premium performance in oil injection systems or for pre-mixing up to 50:1 mix ratio and beyond in outboard and other 2-cycle engines.
- INCREASED SAFETY IN WAREHOUSE STORAGE AND TRANSPORTATION DUE TO HIGHER FLASH POINT. DOES NOT NEED TO BE LABELED "COMBUSTIBLE."



TWO-CYCLE ENGINE OIL

TYPICAL PHYSICAL PROPERTIES

METHOD TYPICAL RESULTS

Viscosity Grade		Two-Cycle Engine Oil		
Gravity, °API	ASTM D287	32.2		
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8644		
Viscosity @ 40°C cSt	ASTM D445	30.07		
Viscosity @ 100°C cSt	ASTM D445	6.15		
Viscosity Index	ASTM D2270	159		
Color	ASTM D1500	Blue		
Zinc, wt. %	ASTM D5185	0		
Sulfur, wt. %	ASTM D4951	0.07		
Sulfated Ash, wt. %	ASTM D874	<0.001		
Nitrogen, wt. %	ASTM D4629	0.47		
TBN, mgKOH/g	ASTM D2896	10		

Description	Pack Size	Part #	Each UPC	Case UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
Two-Cycle Engine Oil	6/1 Quart	516-006	0 14168-01617 9	0 14168-01771 8	L 9.500 x W 7.625 x H 9.625	0.403 / 68.194	12.320 / 1922.300	156 Cases (6 layers of 26)





