

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name:	SL Gear Lub GL5 85w140 16gl
Product Code:	SI551416 (SINCLAIR CODE: 571-005)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:GeRecommendedNorestrictions:Second

Gear Oil Not applicable

### 1.3. Details of the supplier of the safety data sheet

Manufacturer:	Warren Distribution, Inc.	
	727 S. 13th Street	
	Omaha, NE 68102	
<b>Information Phone:</b>	+01 (800) 825-1235	+01 (402) 341-9397
E-mail:	sds@wd-wpp.com	

# 1.4. Emergency telephone numberEmergency phone number:CHEMTREC: +1 (800) 424-9300International: +01 (703) 527-3887

# SECTION 2: Hazards identification

**2.1. Classification of the substance or mixture** Skin Sensitisation Category 1 Hazardous to the aquatic environment - Chronic Category 3

2.2. Label elements GHS Hazard Symbols



Signal Word Hazard Statements	Warning May cause an allergic skin reaction.	
Precautionary Statements	H412 - Harmful to aquatic life with long lasting effects.	
Prevention	<ul> <li>P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> <li>P273 - Avoid release to the environment.</li> </ul>	
Response	<ul> <li>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P302+P352 - IF ON SKIN: Wash with plenty of soap and water.</li> <li>P321 - Specific treatment (see section 4).</li> <li>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</li> <li>P363 - Wash contaminated clothing before reuse.</li> </ul>	
Disposal	P501- Dispose of contents/container in accordance with local/regional/national/international regulations.	
2.3. Other hazards Hazards not otherwise classified:	Avoid prolonged or repeated skin contact with used fluid.	

# Unknown acute toxicity (GHS-US)

<b>SECTION 3: Composition/informat</b>	tion on ingredie	nts
Chemical Name	0/2	C 4 5 #

Chemical Name	%	CAS #	GHS Classification
Residual oils, petroleum, solvent-refined	90 - 99	64742-01-4	Acute Tox. 4; H332
			Acute Tox. 3; H331
Naphthalene	15 - 40	91-20-3	Aquatic Acute 1; H400
			Aquatic Chronic 1; H410
			Acute Tox. 4; H302
			Carc. 2; H351
			Flam. Sol. 1; H228
Cumene	1 - 5	98-82-8	Aquatic Chronic 2; H411
			Asp. Tox. 1; H304
			Acute Tox. 4; H302
			Flam. Liq. 3; H226
			STOT SE 3; H335, H336
Ethyl benzene	1 - 5	100-41-4	Acute Tox. 4; H332
			Flam. Liq. 2; H225
Ethyl acrylate	0.1 - 1	140-88-5	Acute Tox. 4; H312
			Acute Tox. 3; H331
			Acute Tox. 4; H302
			Eye Irrit. 2; H319
			Flam. Liq. 2; H225
			Skin Irrit. 2; H315
			Skin Sens. 1; H317
			STOT SE 3; H335, H336
	1 1 1 1 00	OFD 1010 1000 /IT	

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

SECTION 4: First aid measures			
4.1. Description of first aid measures			
Inhalation Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If			
	breathing, give artificial respiration and have a trained individual administer oxygen and get medical attention immediately.		
Eyes	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the		
	head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical		
	attention and monitor the eye daily as advised by your physician.		
Skin Contact	Wash with soap and water. Remove contaminated clothing, launder immediately, and discard		
	contaminated leather goods. Get medical attention immediately. Seek medical advice if symptoms		
	persist.		
Ingestion	Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of		
	water or milk to dilute.		
4.2. Most important symptor	ns and effects, both acute and delayed		
Symptoms	Not determined		
4.3. Indication of any immediate medical attention and special treatment needed			
Note to Doctor	Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach		
	contents is necessary, use method least likely to cause aspiration.		

### **SECTION 5: Firefighting measures**

5.1. Extinguishing media			
Suitable and Unsuitable	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may		
Extinguishing Media:	cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied		
	to the surface of the fire. Do not direct a stream of water into the hot burning liquid.		
5.2. Special hazards arising from the substance or mixture			
Fire and/or Explosion	Material may be ignited only if preheated to temperatures above the high flash point, for example in		
Hazards	a fire.		
5.3. Advice for firefighters			
Fire Fighting Methods and	Do not enter fire area without proper protection including self- contained breathing apparatus and		
Protection	full protective equipment. Use methods for the surrounding fire.		
Hazardous Combustion	Carbon monoxide, Smoke		
Products			

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

**General Measures:** Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

#### 6.2. Environmental precautions

Do not flush to sewer.

Avoid runoff into storm sewers and ditches that lead to waterways.

Remove from water surface by skimming or with suitable absorbents. Do not use dispersants.

Avoid runoff into storm sewers and ditches that lead to waterways.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up:** Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. {EMSFORM\_06GHS\_CLEAN}

#### 6.4. Reference to other sections

Follow all protective equipment recommendations provided in Section 8.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool dry place. Isolate from incompatible materials.

# Incompatible materialsSee Section 10.7.3. Specific end use(s)

Gear Oil

# **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters	
Chemical Name	Occupational Exposure Limits
Naphthalene	OSHA PEL
Oil mist, mineral	OSHA PEL
Cumene	OSHA PEL
ethylbenzene	OSHA PEL
Ethyl acrylate	OSHA PEL
Naphthalene	OSHA STEL
ethylbenzene	OSHA STEL

#### Value

10 ppm TWA; 50 mg/m3 TWA 5 mg/m3 50 ppm TWA; 245 mg/m3 TWA 100 ppm TWA; 435 mg/m3 TWA 25 ppm TWA; 100 mg/m3 TWA 15 ppm STEL; 75 mg/m3 STEL 125 ppm STEL; 545 mg/m3 STEL

# **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters				
Chemical Name	<b>Occupational Exposure Limits</b>	Value		
Naphthalene	ACGIH TLV-TWA	10 ppm TWA		
Oil mist, mineral	ACGIH TLV-TWA	5 mg/m3		
Cumene	ACGIH TLV-TWA	50 ppm TWA		
ethylbenzene	ACGIH TLV-TWA	20 ppm TWA		
Ethyl acrylate	ACGIH TLV-TWA	5 ppm TWA		
Naphthalene	ACGIH STEL	15 ppm STEL		
Oil mist, mineral	ACGIH STEL	10 mg/m3		
Ethyl acrylate	ACGIH STEL	15 ppm STEL		
Naphthalene	IDLH	250 ppm IDLH		
Cumene	IDLH	900 ppm IDLH (10% LEL)		
ethylbenzene	IDLH	800 ppm IDLH (10% LEL)		
Ethyl acrylate	IDLH	300 ppm IDLH		
Cumene	OSHA PEL-Skin Notation	prevent or reduce skin absorption		
Ethyl acrylate	<b>OSHA PEL-Skin Notation</b>	prevent or reduce skin absorption		
Cumene	OSHA STEL-Skin Notation	Potential for dermal absorption		
Naphthalene	ACGIH TLV-Skin Designation	Skin - potential significant contribution to		
		overall exposure by the cutaneous route		
8.2. Exposure controls				
Engineering Measures				
	handling or using this product to avoid overexposure.			
<b>Respiratory Protection</b>				
or local exhaust ventilation is the preferred means of protection. Use a respirator if general room				
	ventilation is not available or sufficient to eliminate symptoms.			
<b>Respirator Type(s)</b>				
	applicable exposure limits, use NIOSH/MSHA approved respiratory protection.			
Eye Protection	Wear chemically resistant safety glasses with side sh			
<b>.</b>	additional eye protection such as chemical splash go			
	exists for eye contact with splashing or spraying liqu			
	lenses. Have an eye wash station available.			
Skin Protection	Avoid skin contact by wearing chemically resistant	gloves, an apron and other protective equipment		
	depending upon conditions of use. Inspect gloves for			
	intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap			
	and water before eating, drinking, and when leaving work.			
Gloves	Neoprene, Nitrile			

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties		
Physical State	Liquid	
Color	Brown	
Odor	Mild	
Odor threshold	Not determined	
рН	Not determined	
Freezing point	Not determined	
Boiling Point	Not determined	
Flash Point (°C)	218	
Flash Point Method	COC	
Evaporation Rate	Not determined	
Upper Flammable/Explosive	Not established	
Limit, % in air		
Lower Flammable/Explosive	Not established	
Limit, % in air		

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties		
Flammability (solid, gas)	Not applicable	
Vapor pressure	<0.20	
Vapor Density	4.42	
Relative Density	0.9	
Solubility in Water	Negligible; 0-1%	
<b>Octanol/Water Partition</b>	Not determined	
Coefficient		
Autoignition Temperature	Not determined	
<b>Decomposition Temperature</b>	Not determined	
Viscosity(°C)	347.7	
9.2. Other information		
Volatiles, % by weight	0.000000	
volatiles, 70 by weight	0.00000	

# **SECTION 10: Stability and reactivity**

No data available.
Stable under normal conditions.
Hazardous polymerization will not occur.
Temperatures above the high flash point of this combustible material in combination with sparks,
open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Strong oxidizing agents
Carbon monoxide, Smoke

# **SECTION 11: Toxicological information**

11.1. Information on toxicological effects			
Ingestion Toxicity	No hazard in normal industrial use. Estimated to be $> 5.0$ g/kg.		
Skin Contact	This material is likely to be moderately irritating to skin based on animal data. Can cause severe		
	irritation, defatting, and dermatitis. Irritation effects may last for hours or days but will not likely result in permanent damage.		
Absorption	Likely to be practically non-toxic based on animal data.		
Inhalation Toxicity	No hazard in normal industrial use. Estimated to be 2 - 20 mg/l; slightly toxic.		
Eye Contact	This material is likely to be severely irritating to eyes based on animal data. Can cause severe		
	irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain,		
	excess blinking and tear production, with marked redness and swelling of the conjunctiva.		
	Temporary vision impairment (cloudy or blurred vision) is possible.		
Sensitization	Non-hazardous under Respiratory Sensitization category.No data available to indicate product or		
	components may be a skin sensitizer.		
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% is mutagenic		
	or genotoxic.		
Carcinogenicity	Contains a substance that is a possible cancer hazard based on high dose animal studies and/or a		
	human study.		
Reproductive and	No data available to indicate product or any components present at greater than 0.1% may cause		
Developmental Toxicity	birth defects.		
Specific target organ	Non-hazardous under Specific Target Organ Systemic Toxicity Single Exposure category.		
toxicity-Single exposure			
Specific target organ	Non-hazardous under Specific Target Organ Systemic Toxicity Repeated Exposure category.		
toxicity-Repeated exposure			
Aspiration toxicity	Non-hazardous under Aspiration category.		
Other information	No data available.		

# Agents Classified by IARC Monographs Not applicable IARC Group 1

Not applicable	IARC Group 2A
Naphthalene	IARC Group 2B
Cumene	IARC Group 2B
ethylbenzene	IARC Group 2B
Methyl isobutyl ketone	IARC Group 2B
Ethyl acrylate	IARC Group 2B
Vinyl acetate	IARC Group 2B

#### National Toxicity Program (NTP) Status

Not applicable	Known Human Carcinogen
Naphthalene	Reasonably Anticipated To Be A Human Carcinogen
Cumene	Reasonably Anticipated To Be A Human Carcinogen

# **SECTION 12: Ecological information**

```
12.1. Toxicity
```

Acute Aquatic ecotoxicity: Non-hazardous under Aquatic Acute Environment category.
Chronic Aquatic ecotoxicity: H412 - Harmful to aquatic life with long lasting effects.
12.2. Persistence and degradability
Biodegrades slowly.
12.3. Bioaccumulative potential
Bioconcentration may occur.
12.4. Mobility in soil
This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
12.5. Results of PBT and vPvB assessment
No data available.
12.6. Other adverse effects
Not determined

### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Disposal Methods Dispose of by incineration following Federal, State, Local, or Provincial regulations. Waste Disposal Code(s) Waste Description for Spent Product Spent or discarded material is non-hazardous according to environmental regulations. Contaminated packaging: Recycle containers whenever possible. Recycle containers whenever possible.

### **SECTION 14: Transport information**

**DOT Basic** Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO). **Description** 

# **SECTION 15: Regulatory information**

<u>Chemical Inventories</u>	
TSCA Status	All components of this material are on the US TSCA Inventory or are exempt.
U.S. State Restrictions:	Not applicable
WHMIS:	B4, D2A
	B2, D2A

B2, D2A, D2B B2, D1A, D2A, D2B, E, F

Chemical Name	Regulation	CAS #	<b>%</b>
Naphthalene	CERCLA	91-20-3	15 - 40
Benzene, (1-methylethyl)-	CERCLA	98-82-8	1 - 5
ethylbenzene	CERCLA	100-41-4	1 - 5
Ethyl acrylate	CERCLA	140-88-5	0.1 - 1
Naphthalene	SARA 313	91-20-3	15 - 40
Cumene	SARA 313	98-82-8	1 - 5
ethylbenzene	SARA 313	100-41-4	1 - 5
Methyl isobutyl ketone	SARA 313	108-10-1	0.1 - 1
Ethyl acrylate	SARA 313	140-88-5	0.1 - 1
Vinyl acetate	SARA 313	108-05-4	0.001-0.01
None.	SARA EHS		
None.	TSCA 12b		
U.S. State Regulations	<b>D</b>		<b>A</b> (
Chemical Name	Regulation	CAS #	%
Naphthalene	California Prop 65-	91-20-3	15 - 40
	Cancer		
Cumene	California Prop 65-	98-82-8	1 - 5
	Cancer		
ethylbenzene	California Prop 65-	100-41-4	1 - 5
	Cancer		
ISOBUTYL METHYL KETONE	California Prop 65-	108-10-1	0.1 - 1
	Cancer		
Ethyl acrylate	California Prop 65-	140-88-5	0.1 - 1
	Cancer		
Methyl isobutyl ketone (MIBK)	California Prop 65- Dev.	108-10-1	0.1 - 1
	Toxicity		
None.	California Prop 65-		
	Reprod -fem		
None.	California Prop 65-		
Tone.	Reprod-male		
Naphthalene	Massachusetts RTK List	91-20-3	15 - 40
Cumene	Massachusetts RTK List	98-82-8	1 - 5
ethylbenzene Ethylbenzene	Massachusetts RTK List	100-41-4	1 - 5
Ethyl acrylate	Massachusetts RTK List	140-88-5	0.1 - 1
Naphthalene	New Jersey RTK List	91-20-3	15 - 40
Cumene	New Jersey RTK List	98-82-8	1 - 5
ethylbenzene	New Jersey RTK List	100-41-4	1 - 5
Ethyl acrylate	New Jersey RTK List	140-88-5	0.1 - 1
Naphthalene	Pennsylvania RTK List	91-20-3	15 - 40
Benzene, (1-methylethyl)-	Pennsylvania RTK List	98-82-8	1 - 5
Benzene, ethyl-	Pennsylvania RTK List	100-41-4	1 - 5
2-Propenoic acid, ethyl ester	Pennsylvania RTK List	140-88-5	0.1 - 1
None.	Rhode Island RTK List		
Naphthalene	Minnesota Hazardous	91-20-3	15 - 40
	Substance List		
Cumene	Minnesota Hazardous	98-82-8	1 - 5
	Substance List		
ethylbenzene	Minnesota Hazardous	100-41-4	1 - 5
-	Substance List		
Ethyl acrylate	Minnesota Hazardous	140-88-5	0.1 - 1
	Substance List		
	S Ratings:	NFPA Ratings:	
Healt	h: 3	Health: 3	

IIIVIIS Kauli	gs.	
Health:	3	

	Fire:	1	Fire:	1		
	Reactivity:	0	Reactivity:	0		
	PPE:	В				
KEY:	0 - Least	1 - Slight	2 - Moderate	3 - High	4 – Extreme	

#### **SECTION 16: Other information Revision Date** 10/23/2015 10:53:15 AM Supersedes: 6/13/2012 3:19:16 PM References ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association CFR: Code of Federal Regulations DOT: United States Department of Transportation GHS: Globally Harmonized System of Classification and Labeling of Chemicals HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transportation Association IDLH: Immediately Dangerous to Life or Health IMDG: International Maritime Dangerous Goods NFPA: National Fire Protection Association NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration PEL: Permissible Exposure Limit RTK: Right-to-Know SARA: Superfund Amendments and Reauthorization Act STEL: Short-term Exposure Limit TLV: Threshold limit value TSCA: Toxic Substances Control Act TWA: Time weighted average **UN: United Nations** WHMIS: Workplace Hazardous Materials Information System THIS PRODUCT MATERIAL SAFETY DATA SHEET PROVIDES HEALTH AND SAFETY Disclaimer INFORMATION. THE PRODUCT SHOULD BE USED IN APPLICATIONS CONSISTENT WITH THIS PRODUCT LITERATURE. FOR ANY OTHER USES, EXPOSURES SHOULD BE EVALUATED SO THAT APPROPRIATE HANDLING PRACTICES AND TRAINING PROGRAMS CAN BE ESTABLISHED TO ENSURE SAFE WORKPLACE OPERATIONS. THIS MATERIAL SAFETY DATA SHEET IS PROVIDED IN GOOD FAITH AND MEETS THE REQUIREMENTS OF THE HAZARDOUS COMMUNICATION PROVISIONS OF SARA TITLE III AND 29 CFR 1910.1200(g) OF THE OSHA REGULATIONS. THE ABOVE INFORMATION IS BASED ON REVIEW OF AVAILABLE INFORMATION SINCLAIR BELIEVES IS RELIABLE AND IS SUPPLIED FOR INFORMATIONAL PURPOSES ONLY. SINCLAIR DOES NOT GUARANTEE ITS COMPLETENESS OR ACCURACY. SINCE CONDITIONS OF USE ARE OUTSIDE THE CONTROL OF SINCLAIR, SINCLAIR DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, AND ANY LIABILITY FOR DAMAGE OR INJURY WHICH RESULTS FROM THE USE OF THE ABOVE DATA. NOTHING HEREIN IS INTENDED TO PERMIT INFRINGEMENT OF VALID PATENTS AND LICENSES.