



PROCESS 19 INDUSTRIAL OIL

Sinclair Process 19 Industrial Oil is a highly refined, non-compounded paraffinic mineral oil recommended for use as a high-quality process oil or blending component for other lubricants.



FEATURES/BENEFITS

- Uniform quality and chemical composition
- High natural oxidation stability
- Good viscosity-temperature characteristics
- Low volatility
- High flash point
- Good solvency
- Very light color

APPLICATIONS

- Process Oil
- Blending component for other lubricants
- General-purpose lubrication where a non-compounded mineral oil is required



PROCESS 19 INDUSTRIAL OIL

TYPICAL PHYSICAL PROPERTIES

	METHOD	TYPICAL RESULTS
Viscosity Grade		Process 19 Industrial Oil
Gravity, °API	ASTM D287	34.1327
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8543
Viscosity @ 40°C cSt	ASTM D445	20.41
Viscosity @ 100°C cSt	ASTM D445	4.17
Viscosity Index	ASTM D2270	106

Description	Pack Size	Part #	Each UPC	Case UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
Process 19 Industrial Oil	55 Gallon	868-003	0 14168-01719 0	N/A	L 23.000 x W 23.000 x H 35.000	10.715 / 44.444	423.412 / 1693.649	4 Drums

