



SHINGLE OIL

Sinclair Shingle Oil is a water white, low viscosity oil designed for use as a shingle or shake dressing for shake roofs, wooden fencing, wood siding, and log homes. Sinclair Shingle Oil penetrates the wood surface to enhance or replace natural oils and resins leached out by cyclical exposure to sun and rain. Although Sinclair Shingle Oil retards the aging process, it will not renew wood that is already weather damaged.



FEATURES/BENEFITS

- Retards aging process
- Penetrates the wood surface to enhance or replace natural oils

APPLICATIONS

- Shingle or shake dressing
- Used for shake roofs, wooden fencing, wood siding, and log homes
- Loose dirt and debris should be removed before the oil is applied. The roof should be hosed with water 24 hours prior to application to lessen the possibility of over application. Alternatively, a licensed contractor can power wash the roof thereby removing weather damaged wood, allowing oil to absorb into new wood. Sinclair Shingle Oil may be applied by brushing or spraying. The typical application rate is 150-300 square feet per gallon. Application rate depends on the type of wood and the rate at which the oil saturates the wood.
- Do not overapply - Over application may lead to shingle or shake "cupping" and the presence of oil in rainwater runoff. Do not add color pigments - as they will lump and settle out. Do not walk on treated surfaces - Sinclair Shingle Oil is a petroleum oil and is slippery. Do not use on flat surfaces, such as decks. Properly licensed contractors may add certain chemicals, such as antifungal agents and other substances, to Sinclair Shingle Oil. Be sure to find out what safety or health restrictions may apply to these additives.



SHINGLE OIL

TYPICAL PHYSICAL PROPERTIES

	METHOD	TYPICAL RESULTS
Viscosity Grade		Shingle Oil
Gravity, °API	ASTM D287	33.88
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8556
Viscosity @ 40°C cSt	ASTM D445	20.15
Viscosity @ 100°C cSt	ASTM D445	4.13
Viscosity Index	ASTM D2270	107
Color	ASTM D1500	0.5

Description	Pack Size	Part #	Each UPC	Case UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
Shingle Oil	55 Gallon	829-003	0 71621-64917 6	N/A	L 23.000 x W 23.000 x H 35.000	10.715 / 44.444	444.830 / 1779.300	4 Drums

