



# AG DRIP OIL ISO 32

*Sinclair Ag Drip Oil 32 uses ultra-refined, ultra clear Group II base oils. It has the proper stable viscosity for all current drip oilers used to lubricate bearings found on vertical shaft driven deep well turbine pumps. Sinclair Ag Drip Oil 32 contains no harmful additives and will not contaminate underground water supplies. The very high viscosity index minimizes viscosity changes due to temperature variations resulting in a consistent flow of lubrication. Please note that some states or areas may require the use of food grade drip oil. Drip Oil Premium is not H-1 registered for incidental food contact.*



## FEATURES

- **High Viscosity Index:** High viscosity index minimizes viscosity changes related to temperature variations. Ultra refined Group II base oil with no harmful additives to contaminate ground water.
- **Good Cold Flow:** Excellent low temperature fluidity for use at temperature extremes.

## APPLICATION

- **Application:** Sinclair Arctic Fire Ag Drip Oil 32 is recommended for use on deep well turbine pumps that are shaft driven and equipped with a drip oiling mechanism.



# AG DRIP OIL ISO 32

## TYPICAL PHYSICAL PROPERTIES

	METHOD	TYPICAL RESULTS
Viscosity Grade		AG Drip Oil ISO 32
Gravity, °API	ASTM D287	33.7458
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8563
Viscosity @ 40°C cSt	ASTM D445	22.3
Viscosity @ 100°C cSt	ASTM D445	4.52
Viscosity Index	ASTM D2270	117

Description	Pack Size	Part #	Each UPC	Case UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
AG Drip Oil ISO 32	2/2.5 Gallon	764-009	0 14168-01737 4	0 14168-01736 7	L 14.000 x W 9.563 x H 14.375	1.114 / 53.472	38.174 / 1538.786	39 Cases (3 layers of 13)
AG Drip Oil ISO 32	5 Gallon	764-008	0 14168-01648 3	N/A	L 12.500 x W 12.500 x H 15.500	1.402 / 60.083	40.157 / 1686.585	42 Eaches (3 layers of 14)
AG Drip Oil ISO 32	30 Gallon	764-004	0 14168-01714 5	N/A	L 19.500 x W 19.500 x H 29.250	6.437 / 38.056	236.495 / 1182.474	5 Drums
AG Drip Oil ISO 32	55 Gallon	764-003	0 14168-01713 8	N/A	L 23.000 x W 23.000 x H 35.000	10.715 / 44.444	424.099 / 1696.397	4 Drums
AG Drip Oil ISO 32	330 Gallon	764-002	N/A	N/A	L 48.000 x W 48.000 x H 49.000	65.333 / 65.333	2,551.840 / 2551.840	1 Tote

